Aerosmith Fastening Systems



ST4200

Features

- Lightweight only 4.8 lbs
- Depth of Drive Adjustment
- **I** 360° adjustable exhaust deflector
- Uses Aerosmith brand flat wire welded fasteners
- Anti-Double fire mechanism
- Trigger Lock to prevent accidental firing
- Anti-Skid pad
- Shock absorbing comfort rubber handle
- Belt Clip
- Comes with plastic carrying case

Applications

- ▼ Plywood to Steel 14 18 ga (68-43 mil)
- Exterior Gypsum to Steel 14 18 ga (68-43 mil)
- Cement Fiber Board to Steel 14 18 ga (68-43 mil)
- **I** Steel to Steel 14 18 ga (68-43 mil)
- Stucco Lath Applications 14 18 ga (68 43 mil)

Specifications

Height Width Length Weight Recommended Operating Pressure Loading Capacity

Fastener Specifications

Wire Welded Coil Fasteners Shank Diameter Head Diameter Recommended Fasteners Accessories 11-1/4"" (285 mm) 4-2/5" (112.2 mm) 9-1/2" (241.5 mm) 4.8 lbs (2.2 kgs) 70-120 psi (4.9-8.3 bar) Up to 200 fasteners

3/4" – 1-1/2" (19-38 mm) .100" (2.54 mm) .197" - .312" (5.0 – 6.4 mm) Aerosmith Helical, Gripshank Magnetic washer adapter UNM4100A

aerosm