



## PROvantage Weatherproof Subfloor Adhesive

PROvantage™ Weatherproof Subfloor Adhesive is a high-performance, VOC-compliant formula ideal for subfloor installations and general plywood use. It offers a strong initial tack and excellent bond strength for particleboard, OSB, engineered lumber and wet, frozen and treated lumber.

PROvantage Subfloor Adhesive provides a permanent bond that remains flexible, reduces nailing and eliminates squeaky floors. It can be easily extruded from 0°F - 100°F for applications in various climates.

**Exceeds the requirements of APA's AFG-01, ASTM D3498 and ASTM C557.**



### Product Features

- VOC-compliant
- Wet & frozen lumber
- Bridges gaps
- Eliminates squeaks
- Reduces nailing
- Strong, fast grab

### Physical Properties

**Type** Proprietary synthetic polymer

**State** Thixotropic medium viscosity mastic

**Color** Light beige

**Solids** 67%

**Viscosity** 150,000 cps

**Reactive VOC** 49 g/L

**Weight/gallon** 10.6 lbs.

**Flashpoint** < 0°F

**Freeze/thaw stability** Will not freeze

**Storage life** 18 months in tightly closed containers at 75°F

**Coverage (maximum): Approximate length of bead according to bead diameter**

Container	1/8" bead	1/4" bead	3/8" bead
10 oz. Cartridge	123 ft.	30 ft.	13 ft.
28 oz. Cartridge	343 ft.	86 ft.	38 ft.

## Application Guidelines

**Application Temperature** 0°F to 100°F

**Service Temperature Range** -20°F to 120°F

**Method of Application** Cartridge/caulking gun

**Working Time** Approximately 20 minutes for a 1/4" bead

**Working Surfaces** Surfaces to be bonded should be clean, dry and free from excessive oil, grease, water, dirt or any other material that may deter adhesion.

**Cleanup** Tools/adhesive may be cleaned with acetone or mineral spirits. Follow solvent vendor's precautions. NOTE: Test solvent on an out-of-the way area to make sure it will not mar or attack the surface.

## Limitations

Not designed for continuous submersion. Do not use on vinyl-coated drywall, polystyrene foam or rigid plastics. Do not adhere one non porous material to another as this will slow or prevent drying.

## Caution Statements

**DANGER: EXTREMELY FLAMMABLE. VAPOR HARMFUL.** Contains methyl acetate, hexane and residual vinyl acetate. Keep away from heat, sparks and flame. Use only with positive cross-ventilation. Avoid breathing vapors. Do not swallow. Do not allow eye contact or prolonged skin contact. Uncured product can cause eye or skin irritation. Prolonged or repeated overexposure to solvents in uncured product can cause central nervous system, peripheral nervous system, eye, skin, liver kidney or respiratory system effects. **First Aid:** If dizziness or other adverse effects are experienced, move to fresh air; contact physician if discomfort persists. If eye contact occurs, flush eyes with water for 15 minutes; contact physician immediately. If swallowed, do not induce vomiting; contact physician immediately. Wash skin contact areas with soap and water; contact physician if irritation persist. For additional information, refer to Material Safety Data Sheet. **KEEP OUT OF THE REACH OF CHILDREN.**

## Ordering Information

Part No.	Size	Weight	UPC	Case UPC	Units Per Package	Packages Per Pallet
5481	10 Oz. Cartridge	11.60	037083054811	10037083054818	12	108
5482	28 Oz. Cartridge	30.85	037083054828	10037083054825	12	44
5488	52 Gallon Drum	616.35			1	4

**Important Notice:** Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied, is made as to such use or effects incidental to such use, handling or possession or the results to be obtained, whether in accordance with the directions or claimed so to be. The manufacturer expressly disclaims responsibility therefore. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use.

2020 Bruck Street, Columbus, Ohio 43207  
 CUSTOMER SERVICE 1-800-669-4583  
 TECH SERVICE 1-800-347-4583  
 www.titebond.com

**Franklin International**